

Automatic Water Filtration System

ระบบกรองน้ำอัตโนมัติ





INNOVATEK

Water Treatment System

Residential & Commercial Automatic Softener



Tank Size 6" - 70"

Innovatek Automatic softener are built using strong cation resin in high quality corrosion proof FRP Tank&Automatic control value from Pentair water USA.

This system design to remove Hardness from water and can automatically self regeneration setting by timer or water meter. That make Innovatek water filter system easy to operate and maintenance.

- ▷ 100% corrosion proof water filter system for all application
- ▷ Rust proof wound fiber glass/reinforced Polyethylene tank with 150 Psi operating pressure [Burst Test pressure at 600 psi , 250,000 cycle test without leakage]
- ▷ 5 Years warranty on Tank
- ▷ Operating temperature Max 49 degree Celsius

Tank Size (Inch)		Vol. of media (ltrs)	Service flow rate (Cu.m/hr)	Control Valve
H. (Inch)	O.D. (Inch)			
6	13	3	0.3	5810
6	18	5	0.3	5810
6	35	10	0.3	5810
7	35	14	0.4	5810
8	35	18	0.5	5810
9	35	22	0.6	5810
9	40	25	0.6	5810
9	48	30	0.6	5810
10	35	30	0.7	5810
10	54	40	0.7	5810
12	42	50	1.1	5810
12	48	55	1.1	5810
12	52	60	1.1	5810
13	54	75	1.3	5810
14	65	100	1.5	5810
16	65	125	1.9	5810
18	65	175	2.4	5810/5812
21	62	225	3.3	5810/5812
24	65	325	4.3	5810/5812
24	72	425	4.3	5810/5812
30	72	500	6.7	5812/2850
36	72	700	9.6	2850/3150
42	72	950	13.1	3150/3900
48	72	1,300	17.1	3900
63	63	1,300	29.5	3900
70	94	2,500	36.4	3900

More Details



www.filtervision.co.th

Filter Vision Public Company Limited
95 Soi Ramintra 117, Ramintra Rd.,
Minburi, Minburi, Bangkok Thailand 10510
+ (662) 518 2722
+ (662) 518 2723
www.filtervision.co.th



FILTER
VISION
We have solutions



INNOVATEK
Water Treatment System

Residential & Commercial Automatic Sand /Multimedia filter



Tank Size 6" - 70"

Tank Size (Inch)		Vol. of media (ltrs)	Service flow rate (Cu.m/hr)	Control Valve
H. (Inch)	O.D. (Inch)			
6	13	3	0.3	5810
6	18	5	0.3	5810
6	35	10	0.3	5810
7	44	15	0.4	5810
8	44	25	0.5	5810
8	35	18	0.5	5810
9	35	22	0.6	5810
9	40	25	0.6	5810
9	48	35	0.6	5810
10	35	30	0.7	5810
10	54	45	0.7	5810
12	48	55	1.1	5810
13	54	75	1.3	5810
14	65	110	1.5	5810
16	65	125	1.9	5810
18	65	165	2.4	5810/5812
21	62	220	3.3	5810/5812
24	65	250	4.3	5812/2850
24	72	315	4.3	5812/2850
30	72	500	6.7	5812/2850/3150
36	72	700	9.6	2850/3150
42	72	915	13.1	3150 & 3900
48	72	1,300	17.1	3900
63	63	1,300	29.5	3900
70	94	2,500	36.4	3900

Innovatek automatic sand/ multimedia filter are built using genuine Multimedia in high quality corrosion proof FRP Tank & Automatic control value from Pentair water USA. This system design to remove dirt , Turbidity from water and can automatically self cleaning setting by timer or water meter. That make Innovatek water filter system easy to operate and maintenance.

- ▷ 100% corrosion proof water filter system for all application
- ▷ Rust proof wound fiber glass/reinforced Polyethylene tank with 150 Psi operating pressure [Burst Test pressure at 600 psi, 250,000 cycle test without leakage]
- ▷ 5 Years warranty on Tank
- ▷ Operating temperature max 49 degree Celsius

More Details



www.filtervision.co.th

Filter Vision Public Company Limited
95 Soi Ramintra 117, Ramintra Rd.,
Minburi, Minburi, Bangkok Thailand 10510
+(662) 518 2722
+(662) 518 2723
www.filtervision.co.th



FILTER
VISION
We have solutions